



## Truck&Bus Wheels Datasheet

No.	Wheel Size	Part No.	Weight (kg)	Max Load (kg)	Inset (mm)	Outset (mm)	Disc Thickness (mm)	P.C.D (mm)	C.B.D (mm)	Bolt Hole Dia. (mm)	Hand Hole	Single/Dual	Tire	Max Pressure (Kpa)	Valve
1	15X5.0J	RW170	7.4	1000	88	102	14	6-Ø184.15	133	Ø27	/	Dual	185/80R15	650	TR553
2	16X5.5K	RW030	9	1320	102	118	16	6xØ222.25	Ø161	Ø24	/	Dual	215/85 R16	770	TR552
3	16X5.5K		9.5	1320	110	126	16	5xØ203.2	Ø146	Ø29SR22	/	Dual	215/85 R16	770	TR552
4	16X6.0K		9.5	1450	112	128	16	6xØ190	Ø141	Ø20.5SR22	/	Dual	235/85 R16	770	TR552
5	16X6.0K		9.6	1450	121	137	16	6xØ222.25	Ø164	Ø24	/	Dual	235/85 R16	770	TR552
6	17.5x5.25		RW070	10.5	1710	99	115	16	6xØ205	Ø161.2	Ø21	10-Ø53	Dual	7R17.5	830
7	17.5x6.00	13		1750	108	127	19	5xØ203.2	Ø146	Ø32.5SR22	10-Ø46	Dual	8R17.5	760	TR554D
8	17.5x6.00	12.5		1750	116	135	19	6xØ222.25	Ø161	Ø32.5SR22	/	Dual	8R17.5	760	TR554D
9	17.5x6.75	13.2		2000	110	131	21	6xØ205	Ø161	Ø21	/	Dual	9R17.5	850	TR554D
10	17.5x6.75	13.6		2240	116	137	21	6xØ222.25	Ø164.1	Ø32.5SR22	/	Dual	9R17.5	850	TR554E
11	17.5x6.75	12.8		2500	120	141	21	8xØ275	Ø221	Ø24	8-Ø46	Dual	9R17.5	850	TR554E
12	17.5x6.00	RW160	12.5	2500	77	96	19	6xØ205	Ø161.2	Ø26.75	12-Ø46	Dual	8R17.5	830	TR552L
13	19.5x6.00	RW100	15.8	1815	116	135	19	10xØ225	Ø170.2	Ø15.3	/	Dual	225/70 R19.5	850	TR554D
14	19.5x6.75		17.1	2500	115	136	21	6xØ222.25	Ø164	Ø32.5SR22	10-Ø50	Dual	225/70 R19.5	850	TR554D
15	19.5x6.75		16.5	2750	120	141	21	8xØ275	Ø221	Ø26	8-Ø50	Dual	225/70 R19.5	850	TR554D
16	19.5x7.50		17.9	3000	134	156	22	8xØ275	Ø221	Ø32	8-Ø50	Dual	245/70 R19.5	850	TR554D
17	19.5x7.50	RW040	16.7	3000	95	116	21	8xØ275	Ø221	Ø24	8-Ø46	Single	245/70 R19.5	850	TR554D
18	19.5x14.00	RW080	25.5	4500	0	28	28	8xØ275	Ø221	Ø26	8-Ø40	Single	445/65 R19.5	830	TR553E
19	22.5x6.75	RW120	21.2	2800	128	150	22	8xØ275	Ø221	Ø26	8-Ø66	Dual	9R22.5	900	TR554D
20	22.5x7.50	RW010	23	3550	140	162	22	10xØ335	Ø281.2	Ø26	10-Ø61	Dual	245/75 R22.5	978	70MS-7
21	22.5x8.25		24.3	3650	145	168	23	10xØ335	Ø281.2	Ø26	10-Ø61	Dual	11R22.5	978	70MS-7
22	22.5x8.25	RW012	20	3356	147	167.5	20.5	10xØ285.75	Ø220.1	Ø26	10-Ø66	Dual	11R22.5	897	TR554D
23	22.5x8.25	RW012	23.5	3650	145	168	23	10xØ285.75	Ø220.1	Ø26	10-Ø66	Dual	11R22.5	897	TR554D
24	22.5x9.00	RW011	24.8	4125	152.5	176	23.5	10xØ335	Ø281.2	Ø26	10-Ø61	Dual	12R22.5	978	TR554D
25	22.5x9.00	RW011	25.4	4536	152	176	24	10xØ335	Ø281.2	Ø26	10-Ø61	Dual	12R22.5	978	TR554D
26	22.5x9.00	RW010	24	4125	152	175	23	10xØ335	Ø281.2	Ø26	10-Ø61	Dual	12R22.5	978	70MS-7
27	22.5x9.00	RW090	23	4536	79	103	24	10xØ335	Ø281.2	Ø26	10-Ø35	Dual	12R22.5	978	TR552
28	22.5x11.75	RW090	27.6	5000	135	161	26	10xØ335	Ø281.2	Ø26	10-Ø40	Single	385/65 R22.5	897	TR552
29	22.5x12.25	RW090	31.3	5600	119	146	27	10xØ285.75	Ø220.1	Ø26	10-Ø35	Single	425/65 R22.5	897	TR552
30	22.5x9.00	RW180	25.8	4536	152	176	24	10xØ285.75	Ø220.1	Ø26	10-Ø61	Dual	12R22.5	897	TR554D
31	22.5x11.75	RW130	26.9	5000	90	116	26	10xØ335	Ø281.2	Ø26	10-Ø40	Single	385/65 R22.5	897	TR552
32	22.5x11.75	RW020	23.3	4750	0	23	23	10xØ335	Ø281.2	Ø26	10-Ø40	Single	385/65 R22.5	978	TR553E
33	22.5x13.00	RW020	30.3	5700	-14	14	28	10xØ335	Ø281.2	Ø26	10-Ø40	Single	445/65 R22.5	978	TR553E
34	22.5x12.25	RW050	29.6	5600	0	28	28	10xØ285.75	Ø220.1	Ø26	10-Ø40	Single	425/65 R22.5	897	TR553E
35	22.5x13.00	RW050	28.8	5700	0	28	28	10xØ335	Ø281.2	Ø26	10-Ø40	Single	445/65 R22.5	978	TR553E
36	22.5x14.00	RW050	30.8	5800	0	27	27	10xØ335	Ø281.2	Ø26	10-Ø40	Single	455/55 R22.5	897	TR553E
37	24.5x8.25	RW060	27.3	3650	145	168	23	10xØ285.75	Ø220.1	Ø26	10-Ø66	Dual	285/75 R24.5	897	TR555D
38	24.5x8.25	RW060	25.2	3356	145.5	168	22.5	10xØ285.75	Ø220.1	Ø26	10-Ø66	Dual	285/75 R24.5	897	TR555D

Note: The datasheet contains only a part of our products, more sizes please [contact sales@robustwheels.com](mailto:contact.sales@robustwheels.com)